

ADVANCING THE SCIENCE OF SOUND™

RSi

					
System Type	4" Coax	5.25" Coax	6.5" Coax	8" Coax	10" Sub
Frequency Response (-3 dB)	95 Hz - 20 kHz	87 Hz - 22 kHz	85 Hz - 17 kHz	80 Hz - 22 kHz	53 Hz - 175 Hz
Impedance	4 Ω	8 Ω	8 Ω	8 Ω	4 Ω
Max SPL	95.5 dB	105.5 dB	108.0 dB	110.5 dB	105.0 dB
Program Power	20 W	75 W	90 W	125 W	150 W
Coverage	127°	95°	100°	100°	N/A
Sensitivity	85.5 dB	86.5 dB	88.5 dB	89.5 dB	86.0 dB
Height	8.79" / 223.5 mm	11.74" / 298.2 mm	14.31" / 363.5 mm	17.22" / 437.6 mm	17.22" / 437.6 mm
Diameter	7.70" / 195.6 mm	9.68" / 245.9 mm	12.09" / 307.3 mm	14.81" / 376.4 mm	14.81" / 376.4 mm
Weight	5.0 lbs. / 2.3 kg	9.5 lbs. / 4.3 kg	13.5 lbs. / 6.1 kg	20.5 lbs. / 9.3 kg	27.1 lbs. / 12.3 kg
Certifications	UL 1480	UL 1480	UL 1480	UL 1480	UL 1480

HPi

				
System Type	5.25" Coax, High-SPL	8" Coax, High-SPL	12" Coax, High-SPL	12" Coax, High-SPL
Frequency Response (-3 dB)	95 Hz - 22 kHz	93 Hz - 22 kHz	118 Hz - 16 kHz	77 Hz - 19 kHz
Impedance	8 Ω	8 Ω	8 Ω	8 Ω
Max SPL	106.5 dB	115.0 dB	119.0 dB	118.0 dB
Program Power	80 W	125 W	150 W	150 W
Coverage	85°	116°	97°	100°
Sensitivity	87.5 dB	94.0 dB	97.0 dB	96.0 dB
Height	11.74" / 298.2 mm	17.22" / 437.6 mm	17.79" / 452.1 mm	22.80" / 579.1 mm
Diameter	9.68" / 245.9 mm	14.81" / 376.4 mm	18.00" / 457.2 mm	20.80" / 528.3 mm
Weight	9.5 lbs. / 4.3 kg	26.8 lbs. / 12.2 kg	36.1 lbs. / 16.4 kg	35.0 lbs. / 15.9 kg
Certifications	UL 1480 & 2043	UL 1480	UL 1480	-

RS-EZ

						
System Type	3" Full Range	4" Full Range	4" Coax	6.5" Coax	8" Coax	8" Coax, High SPL
Frequency Response (-3 dB)	170 Hz - 14 kHz	185 Hz - 13 kHz	140 Hz - 22 kHz	100 Hz - 22 kHz	100 Hz - 22 kHz	110 Hz - 22 kHz
Impedance	8 Ω	8 Ω	16 Ω	16 Ω	16 Ω	16 Ω
Max SPL	98.0 dB	103.0 dB	100.0 dB	104.0 dB	110.0 dB	111.0 dB
Program Power	20 W	20 W	20 W	32 W	64 W	64 W
Sensitivity	85.0 dB	90 dB	87.0 dB	89.0 dB	89.0 dB	93.0 dB
Height	4.93" / 125.4 mm	8.79" / 223.5 mm	7.85" / 199.6 mm	10.40" / 264.2 mm	12.90" / 327.7 mm	12.90" / 327.7 mm
Diameter	4.35" / 110.5 mm	7.70" / 195.6 mm	7.46" / 189.5 mm	10.07" / 256.0 mm	12.83" / 325.9 mm	12.83" / 325.9 mm
Weight	1.3 lbs. / 0.6 kg	3.9 lbs. / 1.8 kg	3.0 lbs. / 1.4 kg	5.0 lbs. / 2.0 kg	10.0 lbs. / 4.5 kg	10.0 lbs. / 4.5 kg
Certifications	UL 1480	UL 2239	UL 1480, EN54-24	UL 1480, EN54-24	UL 1480	UL 1480, EN54-24

IW

		
System Type	3" Full-Range	5.25" Coax
Frequency Response (-3 dB)	190 Hz - 14 kHz	140 Hz - 22 kHz
Impedance	8 Ω	8 Ω
Max SPL	98.5 dB	106.5 dB
Program Power	20 W	75 W
Coverage	120°	101° Horizontal 100° Vertical
Sensitivity	85.5 dB	87.5 dB
Height	5.00" / 127.0 mm	11.84" / 300.7 mm
Depth	3.50" / 88.9 mm	3.90" / 99.1 mm
Width	5.00" / 127.0 mm	8.64" / 219.5 mm
Weight	3.0 lbs. / 1.4 kg	8.9 lbs. / 4.0 kg
Optional Grilles	Theft resistant stainless steel grille (AC-IW31-TRG)	N/A
Certifications	UL 1480 & 2043	UL 1480 (Back box)

CM-EZ

										
System Type	8" Coax, Snap-Cam Mounting	3" Full-Range	4" Coax	6.5" Coax	6.5" Coax	8" Coax	8" Coax	8" Coax	8" Coax	8" Coax
Frequency Response (-3 dB)	73 Hz - 19 kHz	190 Hz - 14 kHz	160 Hz - 20 kHz	125 Hz - 20 kHz	135 Hz - 22 kHz	92 Hz - 18 kHz	109 Hz - 18 kHz	92 Hz - 18 kHz	109 Hz - 18 kHz	119 Hz - 22 kHz
Impedance	8 Ω	8 Ω	16 Ω	16 Ω	16 Ω	16 Ω	16 Ω	16 Ω	16 Ω	8 Ω
Max SPL	103.5 dB	98.0 dB	100.5 dB	107.0 dB	107.0 dB	107.0 dB	106.0 dB	107.0 dB	106.0 dB	112.0 dB
Program Power	40 W	20 W	20 W	50 W	50 W	64 W	64 W	64 W	64 W	75 W
Coverage	92°	118°	100°	80°	80°	95°	105°	95°	105°	70°
Sensitivity	87.5 dB	85.0 dB	87.5 dB	90.0 dB	90.5 dB	89.0 dB	88.0 dB	88.0 dB	88.0 dB	93.0 dB
Backcan Height	7.50" / 190.5 mm	3.50" / 88.9 mm	3.75" / 95.3 mm	5.75" / 146.1 mm	3.75" / 95.3 mm	5.75" / 146.1 mm	3.75" / 95.3 mm	5.75" / 146.1 mm	3.75" / 95.3 mm	8.00" / 203.2 mm
Diameter	10.75" / 273.1 mm	6.30" / 160.0 mm	7.50" / 190.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm
Weight	7.0 lbs. / 3.2 kg	3.1 lbs. / 1.4 kg	4.0 lbs. / 1.8 kg	8.0 lbs. / 3.6 kg	7.0 lbs. / 3.2 kg	9.0 lbs. / 4.1 kg	7.0 lbs. / 3.2 kg	9.0 lbs. / 4.1 kg	7.0 lbs. / 3.2 kg	9.0 lbs. / 4.1 kg
Certifications	UL 1480 & 2043	UL 1480 & 2043	UL 1480 & 2043, EN54-24	UL 1480 & 2043, EN54-24	UL 1480 & 2043, EN54-24	UL 1480 & 2043	UL 1480 & 2043	-	-	UL 1480 and 2043


CMi

									
System Type	4" Coax	5.25" Coax	6.5" Coax	6.5" Coax, High-SPL	8" Coax	8" Coax	8" Coax, High-SPL	8" Coax, High-SPL	10" Sub
Frequency Response (-3 dB)	90 Hz - 22 kHz	75 Hz - 22 kHz	69 Hz - 22 kHz	73 Hz - 22 kHz	97 Hz - 22 kHz	73 Hz - 22 kHz	80 Hz - 22 kHz	77 Hz - 22 kHz	55 Hz - 118 Hz
Impedance	4 Ω	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω	4 Ω
Max SPL	100.0 dB	105.5 dB	107.5 dB	111.5 dB	111.0 dB	111.5 dB	114.0 dB	114.0 dB	111.0 dB
Program Power	20 W	75 W	90 W	100 W	125 W	125 W	125 W	125 W	150 W
Coverage	95°	105°	110°	100°	120°	125°	105°	110°	N/A
Sensitivity	90.0 dB	86.5 dB	88.0 dB	91.5 dB	90.0 dB	90.5 dB	93.0 dB	93.0 dB	92.0 dB
Backcan Height	6.55" / 166.4 mm	7.75" / 196.9 mm	7.94" / 201.7 mm	7.94" / 201.7 mm	7.94" / 201.7 mm	12.46" / 316.5 mm	7.94" / 201.7 mm	12.46" / 316.5 mm	12.46" / 316.5 mm
Diameter	8.15" / 207.0 mm	10.70" / 272.0 mm	14.75" / 374.9 mm	14.75" / 374.9 mm	14.75" / 374.9 mm	14.75" / 374.9 mm	14.5" / 374.9 mm	14.75" / 374.9 mm	14.75" / 374.9 mm
Weight	5.5 lbs. / 2.5 kg	7.5 lbs. / 3.4 kg	10.1 lbs. / 4.6 kg	12.8 lbs. / 5.8 kg	12.5 lbs. / 5.7 kg	18.8 lbs. / 8.5 kg	14.3 lbs. / 6.5 kg	24.0 lbs. / 10.9 kg	27.1 lbs. / 12.3 kg
Certifications	UL 1480 & 2043	UL 1480 & 2043	UL 1480 & 2043	UL 1480 & 2043	UL 1480 & 2043	UL 1480 & 2043	-	UL 1480 & 2043	UL 1480 & 2043


CM-BGM

				
System Type	5.25" Coax	5.25" Coax	6.5" Coax	8" Coax
Frequency Response (-3 dB)	67 Hz - 20 kHz	90 Hz - 20 kHz	54 Hz - 20 kHz	56 Hz - 18 kHz
Impedance	16 Ω	16 Ω	16 Ω	16 Ω
Max SPL	99.5 dB	98.0 dB	101.5 dB	102.5 dB
Program Power	20 W	20 W	50 W	64 W
Coverage	135°	135°	90°	80°
Sensitivity	83.5 dB	82.0 dB	85.0 dB	84.5 dB
Height	5.75" / 146.1 mm	3.75" / 95.3 mm	5.75" / 146.1 mm	8.00" / 203.2 mm
Visible Diameter	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm
Weight	8 lbs. / 3.6 kg	7 lbs. / 3.2 kg	8 lbs. / 3.6 kg	9 lbs. / 4.1 kg
Certifications	UL 1480 & 2043	UL 1480 & 2043	UL 1480 & 2043, EN54-24	UL 1480 & 2043

SM

												
System Type	3" Full-Range	4" Coax	5.25" Coax	5.25" Coax	5.25" Coax, High-SPL	5.25" Coax, High-SPL	8" Offset, High-SPL	8" Offset, High-SPL	5.25" Coax	5.25" Coax	8" Coax	8" Coax
Frequency Response (-3 dB)	170 Hz - 14 kHz	97 Hz - 22 kHz	86 Hz - 22 kHz	86 Hz - 22 kHz	100 Hz - 22 kHz	100 Hz - 22 kHz	88 Hz - 22 kHz	105 Hz - 22 kHz	65 Hz - 20 kHz	65 Hz - 20 kHz	50 Hz - 20 kHz	50 Hz - 20 kHz
Impedance	8 Ω	4 Ω	4 Ω	4 Ω	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω	8 Ω
Max SPL	98.0 dB	95.5 dB	102.0 dB	102.0 dB	106.0 dB	106.0 dB	115.0 dB	115.0 dB	101.0 dB	101.0 dB	106.0 dB	106.0 dB
Program Power	20 W	20 W	75 W	75 W	80 W	80 W	150 W	150 W	50 W	50 W	75 W	75 W
Coverage	80°	125° Horizontal 125° Vertical	100° Horizontal 100° Vertical	100° Horizontal 100° Vertical	80° Horizontal 85° Vertical	80° Horizontal 85° Vertical	100° Horizontal 70° Vertical	100° Horizontal 70° Vertical	95° Horizontal 100° Vertical	95° Horizontal 100° Vertical	90° Horizontal 105° Vertical	90° Horizontal 105° Vertical
Sensitivity	85.0 dB	82.5 dB	86.0 dB	86.0 dB	87.0 dB	87.0 dB	93.0 dB	93.0 dB	84.0 dB	84.0 dB	87.0 dB	87.0 dB
Height	4.35" / 110.5 mm	9.68" / 245.9 mm	11.40" / 289.6 mm	11.40" / 289.6 mm	11.40" / 289.6 mm	11.40" / 289.6 mm	18.78" / 477.0 mm	18.78" / 477.0 mm	11.88" / 301.8 mm	11.88" / 301.8 mm	18.00" / 203.2 mm	18.00" / 203.2 mm
Width	4.35" / 110.5 mm	6.97" / 177.0 mm	8.63" / 212.3 mm	8.63" / 212.3 mm	8.36" / 212.3 mm	8.36" / 212.3 mm	11.65" / 295.9 mm	11.65" / 295.9 mm	7.50" / 190.5 mm	7.50" / 190.5 mm	11.50" / 292.1 mm	11.50" / 292.1 mm
Weight	1.4 lbs. / 0.6 kg	5.3 lbs. / 2.4 kg	9.5 lbs. / 4.3 kg	9.5 lbs. / 4.3 kg	9.5 lbs. / 4.3 kg	9.5 lbs. / 4.3 kg	21.0 lbs. / 9.5 kg	21.0 lbs. / 9.5 kg	7.4 lbs. / 3.4 kg	7.4 lbs. / 3.4 kg	13.9 lbs. / 6.3 kg	13.9 lbs. / 6.3 kg
Certifications	UL 1480	UL 1480	UL 1480 Testing Planned	UL 1480 Testing Planned	UL 1480 Testing Planned	UL 1480 Testing Planned	UL 1480	UL 1480	UL 1480 & EN54-24 Testing Planned	UL 1480 & EN54-24 Testing Planned	UL 1480 & EN54-24 Testing Planned	UL 1480 & EN54-24 Testing Planned

ADVANCING THE SCIENCE OF SOUND™



	IPD4-CM52-BGM	IPD4-CM62-BGM	IPD-SM500i-II	IPD-SM52-EZ	IPD-SM82-II-EZ	IPD-CM52-BGM	IPD-CM52s-BGM	IPD-CM62-BGM	IPD-CM82-BGM	IPD-RS62-EZ	IPD-RS82-EZ	IPD-HP82-EZ	STNet Switch*
System Type	5.25" Coax	6.5" Coax	5.25" Coax	5.25" Coax	8" Coax	5.25" Coax	5.25" Coax	6.5" Coax	8" Coax	6.5" Coax	8" Coax	8" Coax, High SPL	System Type 16-Port 40 W PoE Switch
Frequency Response (-3 dB)	67 Hz - 20 kHz	54 Hz - 20 kHz	86 Hz - 22 kHz	80 Hz - 20 kHz	50 Hz - 20 kHz	67 Hz - 20 kHz	90 Hz - 20 kHz	54 Hz - 20 kHz	56 Hz - 18 kHz	100 Hz - 22 kHz	100 Hz - 22 kHz	110 Hz - 22 kHz	Power 110-240 VAC, 50/60 Hz
Max SPL	99.0 dB	101.0 dB	102.0 dB	106.0 dB	106.0 dB	99.0 dB	99.0 dB	101.0 dB	103.0 dB	104.0 dB	110.0 dB	111.0 dB	Relay I/O Audible Alarm and Visible Alarm
Coverage	135°	91°	100° Horizontal 100° Vertical	95° Horizontal 100° Vertical	90° Horizontal 105° Vertical	135°	135°	91°	80°	89.0°	81.1°	102°	Height 1.75" / 44.5 mm
Height	5.75" / 146.1 mm	5.75" / 146.1 mm	11.40" / 289.6 mm	11.88" / 301.8 mm	18.00" / 203.2 mm	5.75" / 146.1 mm	3.75" / 95.3 mm	5.75" / 146.1 mm	8.00" / 203.2 mm	10.40" / 264.2 mm	12.90" / 327.7 mm	12.90" / 327.7 mm	Width 17.00" / 431.8 mm
Visible Diameter	11.75" / 298.5 mm	11.75" / 298.5 mm	8.36" / 212.3 mm	7.50" / 190.5 mm	11.50" / 292.1 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	11.75" / 298.5 mm	10.08" / 256.0 mm	12.83" / 325.9 mm	12.83" / 325.9 mm	Depth 9.75" / 247.7 mm
Weight	8 lbs. / 3.6 kg	8 lbs. / 3.6 kg	9.5 lbs. / 4.3 kg	7.4 lbs. / 3.4 kg	13.9 lbs. / 6.3 kg	8 lbs. / 3.6 kg	7 lbs. / 3.2 kg	8 lbs. / 3.6 kg	9 lbs. / 4.1 kg	4.5 lbs. / 2.0 kg	10.0 lbs. / 4.5 kg	10.0 lbs. / 4.5 kg	Weight 67.5 lbs. / 3.1 kg
Certifications	UL 2043	UL 2043	-	-	-	UL 2043	UL 2043	UL 2043	UL 2043	-	-	-	Certifications -



	WLL-TX1-II	WLL-RX1p-II
System Type	Uncompressed wireless transmitter	Uncompressed wireless receiver
Inputs	USB, stereo mini, .25" balanced input connections	Stereo mini (mutes wireless signal when connected)
Outputs	N/A	Euroblock or .25" connections speaker level
Height	1.75" / 44.4 mm	1.75" / 44.4 mm
Depth	6.50" / 165.1 mm	6.50" / 165.1 mm
Width	6.19" / 157.2 mm	6.19" / 157.2 mm
Certifications	-	-

LA



	LA880i	LA880i with LA808i	XT-Spyke*
System Type	3-Way Full Range Line Array	Extended Low Frequency Directivity	2-Way Full Range Line Array
Frequency Response (-3 dB)	71 Hz - 22 kHz	83 Hz - 22 kHz	85 Hz - 20 kHz
Impedance	4 Ω	4 Ω	8 Ω
Max SPL	113 dB	112 dB	115 dB
Program Power	300 W	300 W	150 W
Coverage	91° Horizontal 52° Vertical (500-10k)	90° Horizontal 60° Vertical (200-10k)	120° Horizontal 50° Vertical (500-10k)
Sensitivity	88.0 dB	90.0 dB	92.0 dB
Height	40.87" / 1038.1mm	81.74" / 2076.2mm	37.38" / 949.5mm
Width	7.91" / 200.8mm	7.90" / 200.9mm	6.79" / 172.7mm
Depth	11.99" / 304.5mm	11.99" / 304.5mm	5.50" / 139.7mm
Weight	40.1lbs. / 18.2 kg	74.7lbs / 33.9 kg	17.2lbs / 7.8 kg
Certifications	-	-	-

FP



	FP6020-II	FP6030-II	SS30
System Type	2 x 25 mm High-Directivity	2 x 25 mm High-Directivity	2" / 51 mm High-Directivity
Frequency Response (-3 dB)	170 Hz - 22 kHz	160 Hz - 22 kHz	200 Hz - 18kHz
Impedance	8 Ω	8 Ω	4 Ω
Max SPL	87.0 dB	87.0 dB	92.0 dB
Program Power	15 W	15 W	15 W
Coverage	46°	45°	45°
Sensitivity	75.0 dB	75.0 dB	77.0 dB
Height	8.75" / 222.3 mm	13.1" / 332.7 mm	12.0" / 305.0 mm
Dome Diameter	20.25" / 514.4 mm	30.75" / 781.1 mm	30.0" / 762.0 mm
Weight	5.5 lbs. / 2.5 kg	9.0 lbs. / 4.1 kg	4.5 lbs. / 9.2 kg
Certifications	-	-	-

AMPS



	SA202	SA502	SB335	MA501t	MA3501t	OS-440
Power Per Channel @ < 10% THD	20 W (4 Ω stereo) 10 W (8 Ω stereo)	55 W (8 Ω stereo) 70 W (4 Ω stereo)	35 W 8 Ω (3 channels) 50 W 8 Ω (2 channels)	N/A	N/A	N/A
Power Per Channel @ < 1% THD	15 W (4 Ω stereo) 8 W (8 Ω stereo)	50 W (8 Ω stereo) 65 W (4 Ω stereo)	40 W 8 Ω (3 channels) 55 W 8 Ω (2 channels)	50 W 25V/70V/100V	350 W (4 Ω) 225 W (8 Ω) 350 W 25V/70V/100V	80 W @ 8 Ω 40 W @ 4 Ω (4 Channel)
Bridged mono power @ < 1% THD	N/A	90 W (4 Ω)	N/A	N/A	N/A	
Signal to Noise Ratio	92 dB (100 Hz, 12 dB/oct, 4 Ω, A-Weighted)	>83 dB (50 W)	>84 dB Unweighted	>84 dB Unweighted	>85 dB Unweighted	82 dB
Input Impedance	6k Ω	47k Ω (line level) 600 Ω balanced	10k Ω unbalanced	20k Ω unbalanced 15k Ω balanced	20k Ω unbalanced 10k Ω balanced	12k Ω
Max. Gain	35 dB	34 dB (8 Ω)	34 dB (8 Ω)	N/A	N/A	29.5 dB
Height	1.23" / 31.2 mm	1.25" / 32.0 mm	1.25" / 32.0 mm	1.25" / 32.0 mm	3.50" / 88.9 mm With Feet - 3.75" / 95.2 mm	1.23" / 31.24 mm
Width	3.98" / 101.1 mm	3.90" / 100.0 mm	3.90" / 100.0 mm	3.90" / 100.0 mm	19.00" / 482.6 mm	3.98" / 101.09 mm
Weight (amp only)	0.55 lbs. / 0.25 kg	0.56 lbs. / 0.26 kg	0.93 lbs. / 0.422 kg	1.6 lbs. / 0.73 kg	29.5 lbs / 13.38 kg	3.74 lbs. / 1.69 kg
Certifications	-	-	-	-	-	-

TS



	TSB3.0	TFS1.0	TCE1.5
System Type	2-Way Ultra-Thin Soundbar with EVT™ Intelligibility Control	2-Way Ultra-Thin Front and Surround	2-Way Ultra-Thin Center Channel Eliminator
Tweeter	(3) .75" Silk/Synthetic Soft Dome	0.75" Silk/Synthetic Soft Dome	(2) .75" Silk/SyntheticSoft Dome
Woofer	(6) 3" Polypropylene Ultra-Long Throw w/ NBR Surround	(2) 3" Ultra-Long Throw Polypropylene w/ NBR Surround	(3) 3" Ultra-Long Throw Polypropylene with NBR Surround
Additional Drivers	(2) 1" Patented Woven Synthetic Soft Dome Spatial Field Expanders™	Bass Radiators: (2) 3" Ultra-Long Throw Polypropylene w/ NBR Surround	(2) 3" Ultra-Long Throw Polypropylene with NBR Surround
Frequency Response (-3 dB)	75 Hz - 20 kHz	65 Hz - 20 kHz	65 Hz - 20 kHz
Impedance	8 Ω	8 Ω	8 Ω
Program Power	100 W	100 W	100 W
Sensitivity	90.0 dB	90.0 dB	90.0 dB
Height	6.75" / 171.4 mm	6.75" / 171.4 mm	6.75" / 171.4 mm
Width	43.00" / 1092.2 mm	18.50" / 469.9 mm	26.50" / 673.1 mm
Depth	1.50" / 38.1 mm	1.50" / 38.1 mm	1.50" / 38.1 mm
Certifications	-		-

XT



	XT Surround Stone™ 8*	OctoRock	XT PowerRock*	XT-Spyke*	XT550	XT850
System Type	8" coax	8" Coax	8" 2-way	2-Way Full Range Line Array	5.25" Coax	8" Coax
Frequency Response (-3 dB)	38 Hz - 22 kHz	55 Hz - 20 kHz	45 Hz - 20 kHz	85 Hz - 20 kHz	61 Hz - 9.5 kHz	51 Hz - 10 kHz
Impedance	4 Ω	4 Ω	8 Ω	8 Ω	4 Ω	4 Ω
Max SPL	106.5 dB	109.0 dB	118.0 dB	115 dB	101.0 dB	105.0 dB
Program Power	70 W	200 W	125 W	150 W	60 W	100 W
Coverage	360° Horizontal	n/a	80° Horizontal 80° Vertical	120° Horizontal and 50° Vertical (500-10k)	360° Horizontal 40° Vertical	360° Horizontal 40° Vertical
Sensitivity	88.0 dB	92.0 dB	97.0 dB	92.0 dB	83.0 dB	85.0 dB
Height	14.00" / 355.6 mm	12.5" / 317.5 mm	17.75" / 450.8 mm	37.37" / 949.3mm	15.51" / 394.0 mm	16.42" / 417.1 mm
Diameter	17.25" / 438.1 mm	16.0" / 406.4 mm	n/a	n/a	14.10" / 358.1 mm	14.17" / 359.9 mm
Width	n/a	n/a	17.75" / 450.8 mm	6.80" / 172.7mm	n/a	n/a
Depth	n/a	n/a	14.50" / 368.3 mm	5.5" / 139.7mm	n/a	n/a
Weight	52.6 lbs. / 23.9 kg	32.0 lbs / 15.4 kg	48.0 lbs. / 21.77 kg	17.2 lbs / 7.8 kg	13.0 lbs / 5.9 kg	16.7 lbs / 7.6 kg
Certifications	-	-	-	-	UL 1480	UL 1480

RF



	RF31-EZ-T	RF41-20
System Type	3" Full-Range, Raw-Frame	4" Full-Range, Raw-Frame
Frequency Response (-3 dB)	170 Hz - 14 kHz	155 Hz - 22 kHz
Impedance	8 Ω	8 Ω
Max SPL	98.0 dB	101.5 dB
Program Power	10 W	20 W
Coverage	120°	110°
Sensitivity	85.0 dB	88.5 dB
Height	4.75" / 102.7 mm	2.46" / 62.5 mm
Diameter / Width	4.75" / 120.7 mm	12.59" / 320.0 mm
Weight	1.5 lbs. / 0.7 kg (-T) 2.0 lbs. / 0.9	3.5 lbs. / 1.6 kg
Certifications	UL 1480	-