

## AMX CE-COM2

**Universal Control Extender with 2 Serial Ports** 

CE-COM2 (AMX-CEB003)



## **Overview**

The AMX CE-COM2, Universal Control Extender with 2 serial ports, delivers AMX-quality hardware control to any system that supports IP connectivity. An open control API makes it simple to integrate these boxes with third-party control systems or apps, and the integrated web interface enables configuration without specialized applications. HControl enables them to be auto-discovered and integrated seamlessly with next generation AMX control processors and other HARMAN Professional products.

These universal control extender boxes provide a secure, professional-grade solution for interfacing with serially controlled devices over the network. They are PoE powered, with a small footprint for easy installation and concealment. As a network device, they extend the reach of control processors well beyond the limits inherent in point-to-point connections.

## Features

- Professional-Grade Quality
- Open Control API
- Web Configuration Interface
- Compact Form-Factor
- PoE Powered
- HControl Native

## **Specifications**

GENERAL	
Dimensions (HWD)	1" x 4 1/16" x 4 3/32" (2.5 cm x 10.3 cm x 10.4 cm)
Weight	1 lb (454 g)
	PoE Powered – No local Power Supply needed
Power	Power draw: 1.9 Watts
Operation	(1) RS-232/422/485 control port, supports XON/XOFF, CTS/RTS, 300 - 115.2K Baud
	(1) RS-232 control port, supports XON/XOFF, CTS/RTS, 300 - 115.2K Baud
Status LEDs	<ol> <li>Multicolor LED shows connection and power status</li> <li>Green LED shows Ethernet Link status and activity</li> <li>Red LEDs (1 per COM port) show serial transmit (TX) data activity</li> <li>Yellow LEDs (1 per COM port) show serial receive (RX) data activity</li> </ol>
Connections / Wiring	<ol> <li>(1) RJ-45 ICS-LAN Ethernet Connector</li> <li>(1) 10-Pin 3.5mm captive-screw terminal (RS-232/422/485 port)</li> <li>(1) 5-Pin 3.5mm captive-screw terminal (RS-232 port)</li> </ol>
Certifications	FCC Part 15 Class B CE certification -Including EN 55022 CISPR 22 Class B (+ VCCI/Japan, C-Tick/Aus) RoHS certification REACH certification CP65 certification CB Scheme IEC 62368-1 UL Listing 62368-1



© 2023 Harman. All rights reserved. SmartScale, NetLinx, Enova, AMX, AV FOR AN IT WORLD, and HARMAN, and their respective logos are registered trademarks of HARMAN. Oracle, Java and any other company or brand name referenced may be trademarks/registered trademarks of their respective companies.

AMX does not assume responsibility for errors or omissions. AMX also reserves the right to alter specifications without prior notice at any time. The AMX Warranty and Return Policy and related documents can be viewed/downloaded at www.amx.com. **3000 RESEARCH DRIVE, RICHARDSON, TX 75082 AMX.com | 800.222.0193 | 469.624.8000 | +1.469.624.7400 | fax 469.624.7153** Last Revised: 2023-06-29