



Description

AM 1125 is a 120W mixer-amplifier with 5 audio inputs. Audio input 1 has phantom power supply and get the priority over the other audio inputs through an external command or automatically thanks to the VOX circuit. Dual RCA connectors can be used to link stereo (unbalanced) sound sources (e.g. CD, MP3 players, tuners, etc.). The amplifier output is available both for low impedance loudspeakers (min. 4 Ohm) or 70/100 V constant voltage lines (for loudspeakers with 70/100 V line transformers). It can also be powered by batteries (24 V dc voltage), in order to ensure its proper operation even when the mains supply is unavailable.

Features

- > 160 W power amplifier
- > 4 mic-line inputs and 1 AUX IN
- > VOX facility and phantom power supply on INPUT 1
- > Low and high impedance spekers output
- > Dual RCA connectors for INPUT 4 and AUX IN
- > Ducking control on AUX IN level
- > AUX output on RCA connector
- $\,\,{}^{\backprime}$ Common tone controls on front panel
- > 24 V dc power supply (batteries)

Part Number

12135082 AM 1125


115-230 V

Black


EAN 8024530007638



Line Art 2D







TECHNICAL SPECIFICATIONS

Amplifier s	pecifications	Outpu

Output Power 1 x 120 W @ 4 ohm Output power @ 100 V 1 x 120 W @ 100 V 60 Hz ÷ 15000 Hz Frequency Response (-3dB)

SNR Analog inputs ("A" weighted) >85 dB Crosstalk <85 dB Distortion (THD+N) @ 1 kHz nominal power <1.5 %

Input section Total number of inputs

5 Line inputs 1 RCA Line connectors Mic+Line inputs 4

Mic+Line connectors RCA, XLR Mic+Line Phantom 18 V DC VOX Yes Paging connectors XLR 1 General Purpose Inputs (GPI)

Output section

Signal output number 1 RCA Signal output connectors Power output connectors Euroblock Tone controls Yes

Processing

Configuration Front panel

Configuration and control **Protections**

Cooling Convection

Short circuit Yes Thermal Yes DC Yes **Fuses**

Power requirement

Operating voltage 220-240/115 V~ 50/60Hz

Voltage selection External DC power Yes DC power value 24 V 350 W Power consumption

Technical Specifications Page 2 of 3



Standard compliance

Physical specifications

Safety agency

Cabinet/Case Material

Color

Rack mounting

Size

Height Width Depth Weight CE compliant

Metal Black 19", 2U

88 mm / 3.46 inches 431 mm / 16.97 inches 385 mm / 15.16 inches 7.3 kg / 16.09 lbs

Technical Specifications Page 3 of 3