

DATA SHEET

PARLÉ™ CBC 2500 CM CEILING MOUNTED CONFERENCE AUDIO BAR



The Parlé™ CBC 2500 CM is a ceiling mounted, all-in-one conferencing bar for collaboration spaces where wall mounting might be difficult. Featuring a sleek design that hangs from any open plan ceiling with two discreet cables, the CBC 2500 CM is quickly and cleanly installed with two easy connect mounting points and decorative covers.

With integrated Acoustice Echo Cancellation (AEC) and AI Noise Reduction, the CBC 2500 CM uses a 27-element mic array and Biamp Beamtracking™ technology to actively track and intelligently mix conversations from around the room. Two smart speakers use distortion compensation and dynamic bass enhancement technology to create room filling audio with superior speech reproduction.

The CBC 2500 CM also features Biamp Launch, an automated tuning system that optimizes the audio to each unique conferencing space.

FEATURES

- Beamtracking technology actively tracks and intelligently mixes conversations
- AI noise reduction algorithm for clear voice reproduction
- Low distortion smart speakers
- Biamp Launch for one touch automatic tuning
- LED indications for mute status
- Ceiling mount, cables, and cable cover included
- Certified for Microsoft Teams and Zoom

ARCHITECTS & ENGINEERS SPECIFICATION

The conferencing audio bar shall be designed to work with soft codec conferencing systems. The conferencing audio bar shall include a twenty-seven element digital microphone array. The conferencing audio bar microphones shall offer multidirectional beamforming and automatic signal tracking capabilities. The Beamtracking technology shall operate in conjunction with acoustic echo cancellation technology (AEC) in accordance with US Patent 9659576. The conferencing audio bar shall have two low distortion speakers. The conferencing audio bar shall include dynamic bass enhancement and distortion compensation technology. The conferencing audio bar shall support an automated audio setup process that optimizes audio output levels after physical installation is complete. The conferencing audio bar shall be mountable in an open ceiling application. The conferencing audio bar shall be CE marked, UL listed, and compliant with the RoHS directive. Warranty shall be three years. The conferencing audio bar shall be the Parlé™ CBC 2500 CM.

PARLÉ ABC 2500 SPECIFICATIONS

MICROPHONES		Interfaces	
Microphone Technology:	27-Element Digital Array	USB 3.0:	1x Type C
Frequency Response (100 Hz - 8 kHz):	-10dB	Assistive Listening Feed:	1x 3.5mm mono balanced
Polar Pattern:	Active Beamformed	Power Sources	
Pickup Range (25dBA noise floor):	> 23 feet (7 m)	USB-C:	60W
SNR (@ 1kHz, 94dB SPL, A-Weighted):	69 dB	External Power Supply:	100-240VAC 50/60Hz (12VDC, 4.74A)
Maximum SPL (@ 1kHz, THD < 10%):	130 dB	Overall Dimensions	
Indicators:	Mute Indicator (Green/Red/Off LEDs)	Height:	3.9 inches (100 mm)
Sensitivity (@ 1Pa):	> -37dBFS ± 1dB	Width:	37 inches (940 mm)
Microphone Data Rate Output:	48 kHz	Depth:	2.5 inches (64 mm)
Audio Processing:	AEC (Acoustic Echo Cancellation)	Weight:	9.6 lbs (4.4 kg)
Noise Reduction:	AI filter	Environmental	
LOUDSPEAKERS		Operating Temperature:	32 - 104° F (0 - 40° C)
Frequency Response (57 Hz - 20 kHz):	-10 dB	Humidity:	0-90% (non-condensing)
Nominal Beamwidth (H x V):	180° x 180°	Altitude:	0-10,000 ft (0-3000m) MSL
Transducers:	2x 2.5 in (60 mm) full range	Compliance:	
Rated Maximum SPL (@ 1m):	90 dB (continuous) 96 dB (peak)	FCC Part 15B (USA)	
Sensitivity (@ 1m, 2.83V):	84 dB	CE Marked (Europe)	
THD (@ 1kHz):	< 0.2%	UL and C-UL listed (USA and Canada)	
Nominal Impedance:	4Ω	RoHS Directive (Europe)	
Continuous Rated Power (6 dB crest factor, HPF @ 60 Hz):	20W		
Sampling Rate:	48 kHz		

PARLÉ CBC 2500 CM SPECIFICATIONS

Bundle Contents:	(1) Parlé ABC 2500 Bar
	(1) Mounting plate with center plug
	(2) Decorative cable covers 39" (1m)
	(2) Aircraft Bables 10' (3m)
	(2) Cable grippers with quick connect
	(2) Eye bolts (Lag Screw Type)
	(1) USB 3.0 cable 33" (10m)
	(1) Power extender 33" (10m)

Biamp strives to improve its products on a continual basis. Specifications are therefore subject to change without notice.

Biamp, Devio, and Parlé are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.